

# Bảng thông số sản phẩm

Thông số kỹ thuật

**APC**

Green  
Premium™



APC Smart-UPS On-Line, 3kVA,  
Tower, 230V, 8x C13+2x C19  
IEC outlets, SmartSlot, Extended  
runtime, W/O rail kit

SRT3000XLI

## Overview

|              |   |
|--------------|---|
| Presentation | High density, double-conversion on-line power protection with scalable runtime. |
| Lead time    | Usually in Stock  |

## Main

|                        |  |
|------------------------|--|
| Main Input Voltage     | 230 V  |
| Other Input Voltage    | 220 V<br>240 V   |
| Main Output Voltage    | 230 V  |
| Other Output Voltage   | 220 V<br>240 V   |
| Rated power in W       | 2700 W   |
| Rated power in VA      | 3000 VA  |
| Plug standard          | BS1363A British<br>IEC 60320 C20<br>Schuko CEE 7 / EU1-16P   |
| Output connection type | 8 IEC 60320 C13<br>2 IEC Jumpers<br>2 IEC 60320 C19  |
| Cable length           | 2.44 m   |
| Number of cables       | 3  |
| Battery type           | Lead-acid battery  |
| Provided equipment     | CD with software<br>Country-specific detachable power cord<br>Documentation CD<br>Installation guide<br>Removable support feet<br>USB cable<br>Warranty card |

## General

|                                     |              |
|-------------------------------------|--------------|
| Product web sub-family              | High density |
| Number of power module free slots   | 0            |
| Number of power module filled slots | 0            |
| Redundant                           | No           |

## Physical

|                     |                       |
|---------------------|-----------------------|
| Colour              | Black                 |
| Height              | 43.2 cm               |
| Width               | 8.5 cm                |
| Depth               | 63.5 cm               |
| Net weight          | 31.3 kg               |
| Mounting location   | Front                 |
| Mounting preference | Lower                 |
| Mounting mode       | Rack-mounted with kit |
| Two post mountable  | 0                     |
| USB compatible      | Yes                   |
| Mounting position   | Vertical              |

## Input

|                      |                                    |
|----------------------|------------------------------------|
| Network frequency    | 40...70 Hz auto-sensing            |
| Input voltage limits | 100...275 V adjustable (half load) |

## Output

|                                  |  |
|----------------------------------|--|
| Maximum configurable power in W  | 2700 W                                 |
| Harmonic distortion              | Less than 2 %                          |
| Output frequency                 | 50/60 Hz +/- 3 Hz sync to mains        |
| Crest factor                     | 3 : 1                                  |
| UPS type                         | Double conversion online               |
| Wave type                        | Sine wave                              |
| Bypass type                      | Internal bypass (automatic and manual) |
| Maximum configurable power in VA | 3000 VA                                |

## Conformance


|                        |  |
|------------------------|--|
| Product certifications | CE<br>EAC<br>RCM<br>VDE  |
| Marking                | CE Mark  |
| Standards              | EN/IEC 62040-1:2019/A11:2021<br>EN/IEC 62040-2:2006/AC:2006<br>EN/IEC 62040-2:2018 |

## Environmental

|                                       |                         |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C               |
| Relative humidity                     | 0...95 % non-condensing |
| Operating altitude                    | 0...10000 ft            |
| Ambient air temperature for storage   | -15...45 °C             |
| Storage Relative Humidity             | 0...95 % Non-condensing |
| Storage altitude                      | 0.00...15240.00 m       |

|                         |           |
|-------------------------|-----------|
| Acoustic level          | 55 dBA    |
| Heat dissipation        | 703 Btu/h |
| IP degree of protection | IP20      |

## Batteries & Runtime

|  |  |
|--|--|
| Battery recharge time                  | 3 h  |
| Number of battery replacement quantity | 1  |
| Additional information                 | Configurable for 220 : 230 or 240 nominal output voltage   |
| Battery voltage                        | 96 V   |
| Battery charger power                  | 168 W rated  |
| Battery power in VAH                   | 505 VAh runtime  |
| Battery life                           | 3...5 year(s)  |
| Replacement battery                    | <a href="#">APCRBC152</a>   |
| Battery option                         | SRT96BP 1 1515 VAh<br>SRT96BP 2 2525 VAh<br>SRT96BP 3 3535 VAh<br>SRT96BP 4 4545 VAh<br>SRT96BP 5 5555 VAh<br>SRT96BP 6 6565 VAh<br>SRT96BP 8 8585 VAh<br>SRT96BP 10 10605 VAh |
| Extended runtime                       | 1  |

## Communications & Management

|                     |  |
|---------------------|--|
| Free slots          | 1  |
| Control panel       | Multifunction LCD status and control console       |
| Alarm               | Audible and visible alarms prioritized by severity |
| Emergency power off | Yes  |

## Surge Protection and Filtering

|                   |       |
|-------------------|-------|
| Surge energy rate | 340 J |
|-------------------|-------|

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 24.6 cm  |
| Package 1 Width              | 87.1 cm  |
| Package 1 Length             | 59.9 cm  |
| Package 1 Weight             | 36.74 kg |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product                            |
| REACH Regulation           | <a href="#">REACH Declaration</a>                |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>                              |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>    |

---

|                                    |   |
|------------------------------------|---|
| <b>Circularity Profile</b>         | <a href="#">End of Life Information</a>   |
| <b>WEEE</b>                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| <b>Optimized Energy Efficiency</b> | Energy efficient product  |
| <b>Take-back</b>                   | Take-back program available   |

---

## **Contractual warranty**

---

|                 |   |
|-----------------|---|
| <b>Warranty</b> | 3 years repair or replace (excluding battery) and 2 years for battery |
|-----------------|---|

**Thay thế được đề xuất**