

# Bảng thông số sản phẩm

Thông số kỹ thuật



## APC Easy UPS On-Line SRV 10000VA 230V with Extended Runtime Battery Pack

SRV10KIL

### Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

### Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	10000 W
Rated power in VA	10000 VA
Output connector type	Hard wire 3-wire (1P + N + E) 1
Provided equipment	1 USB cable 1 RS-232 configuration cable 1 external battery pack 1 battery cable user manual

### General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

### Physical

Colour	Black (RAL 7010)
Height	36.8 cm
Width	38 cm
Depth	48.5 cm
Net weight	76.5 kg
Mounting location	Front
Mounting preference	No preference

<b>Mounting mode</b>	Not rack-mountable
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Vertical

## Input

<b>Input voltage limits</b>	110...300 V half load 176...300 V full load
<b>Number of input connectors</b>	1 hard wire 3-wire (1P + N + E)
<b>Network frequency</b>	40...70 Hz auto sensing

## Output

<b>Maximum configurable power in VA</b>	10000 VA
<b>Maximum configurable power in W</b>	10000 W
<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains
<b>Harmonic distortion</b>	1 %
<b>UPS type</b>	Double conversion online
<b>Wave type</b>	Sine wave
<b>Efficiency</b>	94 % (full load)
<b>Additional information</b>	Configurable for 220 : 230 or 240 nominal output voltage
<b>Bypass type</b>	Internal bypass (automatic and manual)
<b>Crest factor</b>	3 : 1

## Conformance

<b>Product certifications</b>	CE UKCA EAC TISI
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
<b>Relative humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...3000 m
<b>Ambient air temperature for storage</b>	-15...60 °C
<b>Storage Relative Humidity</b>	Non-condensing 0...95 %
<b>Storage altitude</b>	0...15000 m
<b>Acoustic level</b>	58 dB
<b>Heat dissipation</b>	2128 Btu/h
<b>IP degree of protection</b>	IP20

## Batteries & Runtime

<b>Battery type</b>	Lead-acid battery
<b>Battery voltage</b>	240 V

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	9 h
Battery life	3...5 year(s)
Battery charger power	1170 W rated
Battery option	SRV240BP-9A 1 3024 VAh SRV240BP-9A 2 4536 VAh SRV240BP-9A 3 6048 VAh SRV240BP-9A 4 7560 VAh

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1

## Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46 cm
Package 1 Width	57 cm
Package 1 Length	58 cm
Package 1 Weight	82.5 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Thay thế được đề xuất